# 1998 EDITORIAL INDEX

## COMMUNICATIONS


• Wired communications braces for the age of multimedia (April, p. 33)
• Wireless looks ahead to the millenium (April, p. 43)
• MMIC circuits enable direct-carrier modulation, Part 1 (April, p. 113)
• MMIC circuits enable direct-carrier modulation, Part 2 (May, p. 157)
• LMDS technology advances through FCC auction (June, p. 48)
• The wide world of wireless heads for generation 3 (August, p. 31)
• Wireless communication chips span the semiconductor gamut (October, p. 31)
• Superconductors improve coverage in wireless networks (April, p. 63)
• Are wild times ahead for wireless in 1999? (December, p. 35)
• Wireless data system gives cops the edge (December, p. 54)


## COMPONENTS


• Analysis method characterizes microwave oscillators (January, p. 71)
• Designing amplifiers for wireless systems (January, p. 89)
• Amplifiers operate on medical applications (January, p. 168)
• Minimize EMI effects in wireless circuits (February, p. 54)
• Analysis method characterizes microwave oscillators (February, p. 65)
• Power amps offer design flexibility in PCS applications (February, p. 84)
• Understanding handset power-amplifier trade-offs (February, p. 94)
• Synthesize matching networks for LNAs and power amplifiers (February, p. 105)
• Pair of amps powers cellular/PCS handsets (February, p. 162)
• Matrix switches enhance ATE system performance (February, p. 164)
• Vector modulator enhances feedforward cancellation (March, p. 83)
• IF amp offers novel gain-control function (March, p. 93)
• Design a directional coupler using a sinusoidal coefficient (March, p. 150)
• Dual-band amplifiers extend EMC testing (March, p. 197)
• YIG filters tune from 3 to 40 GHz (March, p. 202)
• Silicon gain blocks require only +3 VDC (March, p. 205)
• Bandpass ADC supports RF receiver designs (March, p. 210)
• Deriving amplifier gain-control characteristics (April, p. 93)
• Finline oscillator offers millimeter-wave operation (April, p. 103)
• Demodulating logamps bolster wide-dynamic-range measurements (April, p. 127)
• Optical components handle high-speed data (April, p. 139)
• Magnetic latch leads to long switch life (April, p. 177)
• Antenna technology's beams radiate in many directions (May, p. 37)
• New consortium brings wireless packaging design issues into focus (May, p. 112)
• Wideband antenna design serves wireless systems (May, p. 115)
• Predict the effects of ADC-clock phase noise (May, p. 123)
• Analyze and design a cascode MESFET mixer (May, p. 129)
• Assessing IF-amplifier linearity performance (May, p. 142)
• Select a mechanical RF relay or switch (May, p. 183)
• SAW-filter line supports diverse wireless standards (May, p. 246)
• Power combiners expand transmitter capacity (May, p. 250)
• Driver amplifiers include equalizers (May, p. 252)
• Power amplifiers target wireless communications (May, p. 254)
• Amplifiers spur North American product tour (May, p. 256)
• Superconducting filters enhance military receiver performance (June, p. 61)
• Feedforward correction reduces IMD in broadcast ampli-

fiers (June, p. 71)
• Filter design enables amplifier selectivity function (June, p. 93)
• High-speed data capture needs fast ADCs and special storage (June, p. 110)
• TO-5 bypass relays reach past 3 GHz (June, p. 164)
• Receive filter assembly passes AMPS B-band (June, p. 167)
• Thermal design ensures RF power-amp reliability (July, p. 55)
• Amplifier technology simplifies wireless designs (July, p. 77)
• Circuits control IF-amplifier modulator functions (July, p. 87)
• RF CMOS circuits target IMT-2000 applications (July, p. 99)
• Choosing passive components for high-power amplifiers (July, p. 109)
• HBT power amplifier drives CDMA/AMPS handsets (July Cover, p. 128)
• SMA connector system interchanges transition pins (July, p. 144)
• Connectors fit video and cellular cables (July, p. 146)
• Antenna design is based on the method of moments (August, p. 55)
• Tests evaluate the influence of junctions on PIM (August, p. 70)
• Prototype circuit demonstrates IF-VGA gain characteristic (August, p. 81)
• Considering loss in RF amplifier splitters/combiners (August, p. 107)
• LDMOS multicarrier amplifier powers cellular base stations (August, p. 175)
• LNA quiets mobile satcom receivers (August, p. 176)
• Subharmonic mixers simplify digital-modulation systems (September, p. 62)
• Coupler design delivers low-ripple performance (September, p. 72)
• Oscillator offers wide data bandwidth and high noise rejection (September, p. 77)
• Linear amp achieves wide dynamic range (September Cover, p. 132)
• Sources quell phase hits in digital radios (September, p. 143)
• Tiny YIG filters screen portable systems (September, p. 148)
• Converter circuit provides size and cost reduction (October, p. 83)
• Multi-harmonic method optimizes power amplifiers (October, p. 92)
• Compute power rating for unmatched lines (October, p. 100)
• Predistorter linearizes CDMA power amplifiers (October, p. 114)
• Dual-band, 3-VDC amp addresses tough design challenges (October Cover, p. 126)
• Fast design approach yields 8.75-GHz multiplier (October, p. 152)
• Changing times challenge the crystal industry (November, p. 31)
• Feedback technique improves oscillator phase noise (November, p. 61)
• Understand the effects of retrace and aging in OCXOs (November, p. 72)
• CPW-based circuits deliver broadband performance (November, p. 79)
• Corralling the correct crystal oscillator (November, p. 94)
• Low-noise amp fronts for high-speed ADC (November, p. 122)
• Variable pads embody new design approach (November, p. 134)
• Methods linearize RF transmitters and power amps (December, p. 102)
• Design guidelines minimize erosion in SMA connectors (December, p. 132)
• MMIC amplifier powers 38-GHz links (December, p. 250)
• Power amplifiers boost radio links (December, p. 252)

## ◀ COMPUTER-AIDED ENGINEERING ▶

• Smith chart software eases circuit analysis (February, p. 158)
• Check the accuracy of a system simulator (May, p. 175)
• Webwatch section (May, p. 193)
• EM simulator adds optimization (June, p. 123)
• Extract MESFET models for wireless applications (June, p. 127)
• System simulator incorporates DSP tools (June, p. 137)
• Software synthesizes transmission lines (June, p. 140)
• Math software improves symbolic interface (July, p. 136)
• Math software provides tracking-loop simulation (August, p. 86)
• System simulator speeds design of CDMA amplifier (August, p. 96)
• Reference CD-ROM tackles EMC problems (August, p. 182)
• Software enhances automated load-pull measurements (September, p. 89)
• Software delivers accurate noise simulation (October, p. 73)
• Software speeds load-pull testing (October, p. 140)
• Software simplifies ISO9000 certification (October, p. 150)
• Design suite speeds circuit, EM simulations (November, p. 128)
• Software maps RF propagation (November, p. 130)
• High-speed design section (December, p. 173)
• Webwatch section (December, p. 207)
• Software guides custom ISO9000 processes (December, p. 215)

• Software tracks mixer spurious products (December, p. 219)
• Program facilitates toroid design (December, p. 222)
• Software helps visualize matrix functions (December, p. 225)

## ◀ CONFERENCES ▶

• Digital technology rules at WIRELESS Symposium (March, p. 35)
• Mobile computing heads Portable-By-Design Show (March, p. 45)
• Technology continues to evolve at Sixth WIRELESS Symposium (March, p. 158)
• Products display advancing technology, declining price (March, p. 168)
• 1998 International Microwave Symposium (May, p. 66)
• Communications growth prods new product development (May, p. 95)
• NIST workshop reviews support for industry (August, p. 40)
• WIRELESS Symposium comes to Boston (August, p. 119)
• Amsterdam hosts triple MW conference (August, p. 138)
• European conference takes wireless focus (August, p. 142)
• WIRELESS Symposium sounds calls for more competition (October, p. 40)
• Device technology advances at 44th IEDM (November, p. 41)
• Wembley exhibition boasts key product introductions (December, p. 47)
• Program promises wireless innovations (December, p. 141)
• Wireless products address the growth of applications (December, p. 159)

## ◀ CROSSTALK ▶

• Keith Gilbert, president and CEO of Stellex Microwave Systems (April, p. 47)
• Paul Davidsson, president and a co-founder of RF Power Components, Inc. (May, p. 49)
• Richie Faubert, Vice President for the Television/Communications Business Unit of Tektronix, Inc. (October, p. 47)
• Tom Parker, Managing Director of US operations of Filtronic, plc. (November, p. 45)

## ◀ DEFENSE ELECTRONICS ▶

• Military retrenchment spells electronics growth (June, p. 37)
• Modern military technology gets a commercial look (September, p. 31)

## ◀ DEVICES & ICS ▶

• Determine the loss of discrete baluns (January, p. 103)
• RF ICs augment supplier's DSP lines (January, p. 166)
• Integration leads to leaner, more-digital cell phones (February, p. 31)
• Integrated circuit simplifies the design of VCOs (February, p. 75)
• Discrete devices grow in power (February, p. 115)
• Low-voltage RF IC amps drive handset applications (February, p. 141)
• PLL line augmented by fractional-N ICs (February, p. 153)
• LDMOS transistor powers base-station amplifiers (March, p. 69)
• Handset chip set delivers dual-mode, dual-band operation (March, p. 190)
• LDMOS transistor powers PCS base-station amplifiers (April, p. 77)
• Design a single-chip, low-noise crystal oscillator (April, p. 133)
• Dual-chip solution targets GSM handsets (April, p. 164)
• Foundry fabricates GaAs HBT circuits (April, p. 168)
• Three-chip set is low-cost solution for wireless data (April, p. 179)
• DDS IC integrates reference multiplier (May, p. 235)
• CMOS technology adjusts to RF applications (June, p. 79)
• GaAs product line debuts with HBT ICs (June, p. 156)
• Circuits integrate wireless RF functions (June, p. 160)
• Surface-mount synthesizer operates to 2.5 GHz (June, p. 163)
• Stand-alone DDS cuts spurs to –60 dBc (June, p. 166)
• GaAs, MOS, bipolar vie for power applications (July, p. 31)
• RFID technology puts zip in the mail (July, p. 41)
• IMD parameters describe LDMOS device performance (July, p. 69)
• Power-amplifier MMICs drive commercial circuits (July, p. 116)
• ASIC automatically controls bipolar bias (July, p. 140)
• Understanding LDMOS device fundamentals (August, p. 114)
• Wide-range ADC samples CDMA signals (August Cover, p. 158)
• Three-dimensional designs drive company's resurgence (August, p. 180)
• Modulator/synthesizer features low spurious content (August, p. 190)
• Single IC contains driver and power FETs (October, p. 133)
• Radio receiver IC reduces system costs (October, p. 136)
• Process refinements benefit power FETs (October, p. 142)
• Relate LDMOS device parameters to RF performance (November, p. 88)
• Single-chip design forms complete PLL synthesizer (November, p. 116)

## ◀ MATERIALS ▶

• BeO packages house high-power components (March, p. 111)

• BeO packages house high-power components, Part 2 (April, p. 107)
• Aluminum-based metallization enhances device reliability (October, p. 61)
• Low-cost substrates offer high performance (October, p. 144)
• Stable materials cut high-frequency losses (October, p. 148)
• Surface-mount packages extend diodes past 5.8 GHz (December Cover, p. 234)

## ◀ SYSTEMS & SUBSYSTEMS ▶

• Fractional-N synthesizers trim current, phase noise (February Cover, p. 126)
• Flexible systems speed phase-noise testing (February, p. 137)
• BWOs power mm-wave sweep generators (February, p. 156)
• Spread-spectrum system provides positioning data (March, p. 63)
• Single platform tests systems-on-a-chip (March, p. 198)
• High-speed DSP solves system needs (March, p. 200)
• Time/frequency standard uses GPS signals (April, p. 89)
• Fractional-N methods tune base-station synthesizer (April Cover, p. 151)
• Fiber-optic modules support PCS systems (April, p. 175)
• Evaluate the impact of phase noise on receiver performance, Part 1 (May, p. 165)
• Evaluate the impact of phase noise on receiver performance, Part 2 (June, p. 101)
• System emulates satellite signals (June, p. 151)
• VXI receivers scan VHF/UHF range (August, p. 168)
• ECM receiver integration reduces package size (August, p. 184)
• System simulates monopulse target returns (August, p. 186)
• Access To The Internet Goes Through Outer Space (September, p. 38)
• Approach performs RF detection directly (September, p. 84)
• Board-level modem reduces design time (September, p. 150)
• Evaluation board holds fractional-N synthesizer (September, p. 152)
• Module recovers and retimes 2.488-Gb/s data (November, p. 132)

## ◀ TEST & MEASUREMENT ▶

• Calibrating changes in test equipment (January, p. 32)
• Improve digital system testing with adaptive equalization (January, p. 57)
• Millimeter-wave testing satisfies compliance standards (January, p. 83)
• Analyze QAM signals with oscilloscope eye diagrams (January, p. 115)
• Oscilloscope buyer's guide (January, p. 135)
• Prober automates shielded RF wafer measurements (January Cover, p. 151)
• Portable instrument tames digital video testing (January, p. 160)
• Hand-Held power meter takes to the field (January, p. 164)
• Analyzers perform passive-IM testing (February, p. 149)
• Interpret IS-98A test needs for CDMA phones (March, p. 101)
• Creating CDMA signals for amplifier testing (March, p. 127)
• Demodulating logamps bolster wide-dynamic-range measurements (March, p. 137)
• CDMA signal generator improves amplifier testing (March Cover, p. 178)
• Measurement system speeds CDMA phone development (March, p. 188)
• Vector analyzer gains in speed (March, p. 194)
• Handheld meter surveys EM fields (March, p. 214)
• Handheld analyzer checks RF field strength (April, p. 172)
• Fast frequency synthesizers speed production testing (May Cover, p. 229)
• Synthesizer races from 1 to 3200 MHz (May, p. 248)
• Peak power meter probes wide bandwidths (June Cover, p. 147)
• Digital phosphor oscilloscopes simplify complex-signal analysis (June, p. 161)
• Signal analyzer embeds scope-like test power (June, p. 165)
• Modulation source aids vector signal generators (July, p. 138)
• Averaging methods influence spectrum-analyzer accuracy (August, p. 64)
• Automated methods provide antenna-gain measurement (September, p. 49)
• Trends in test equipment section (September, p. 97)
• Eight-channel DSO combines high speed and long memory (October, p. 138)
• Flexible instrument tests wireless transmitters (November Cover, p. 108)
• Vector analyzers pare test time (November, p. 124)
• Tests ensure reliable CDMA repeater operation (December, p. 69)
• Understand the basics of WCDMA signal generation (December, p. 83)
• Analysis examines the effects of coupler mismatch (December, p. 89)
• Tracking error sources in HTS filter simulations (December, p. 119)
• High-speed design section (December, p. 173)
• Comprehensive analyzer integrates multiple functions (December, p. 246)